


Combination arrester, 1-pole + NPE with remote signalling



V 25-B+C/...: Combination arrester set, lightning and surge arrester Type 1+2 to DIN EN 61643-11 (B+C to VDE 0675 part 6)

- With new MultiBase base part and Multi-connection clamps
- Complete unit consisting of upper part and base, pre-mounted and ready for connection
- Suitable for any TN and TT network systems
- With remote signalling, potential-free changeover contact, for function monitoring
- Plug-in arrester with dynamic separating device
- Visual function display
- Voltage protection level < 0,9 kV
- Enclosed, non-extinguishing zinc varistor arrester for use in normal commercial distributor housings
- Marked connections
- -FS variant with remote signalling contact (potential-free NO contact)


Dimensions



Application example: building with an overhead power line supply or lightning protection system, for building up lightning protection equipotential bonding.

Type	Highest continuous voltage V	Version	Pack. pcs	Weight kg/100 pcs.	Item No.
V25-B+C 1+NPE+FS	280	1+NPE with FS	1	27,500	5094444

Connection options



V25-B+C 1+NPE+FS

Nominal voltage V	U_N	230
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0+2
Impulse discharge current (10/350) kA	I_{imp}	7
Total discharge current (10/350) kA	I_{total}	14
Nominal discharge current (8/20) kA	I_n	30
Arrester surge current (8/20) [total] kA	$I_{Total 8/20}$	60
Maximum discharge current (8/20 μ s) kA	I_{max}	50
		–
Voltage protection level kV	U_p	< 0,9
Response time ns	t_A	< 25
Maximum back-up fuse A		160
Temperature range °C	ϑ	-40+80
Division unit TE (17.5 mm)		2
Protection rating		IP20
Connection cross-section rigid mm ²		2,5-35
Connection cross-section, multi-wire mm ²		2,5-35
Connection cross-section, flexible mm ²		2,5-25